

Saving 120 tonnes of CO₂

Stadthaus Murray Grove in London Waugh Thistleton Architects, London



forms filled with concrete. The facades are clad with fibre-cement panels, shaded from white to black, inspired by a painting by Gerhard Richter from 1999. Waugh Thistleton architects regard this new building as setting a precedent - nowhere else in Europe has a residential building in timber of anything like this height been authorised for construction. The construction method was worked out by the architects in cooperation with engineers Meghan Yates and Matt Linegar from Techniker Ltd., London. Indeed, the method was sufficiently new to the British building authorities for it now to be incorporated in the building regulations as an appendix. Meeting building code requirements for fire was

Probably the world's tallest timber-framed

residential building was completed in re-

cent months in the suburb of Hackney, in

Grove Housing Development, stands

East London. Stadthaus, part of the Murray

29.75 metres high; it has nine storeys, one

ments. Apart from the plinth, which is of reinforced concrete, the entire building, in-

with shops, three for social housing and

five with independently financed apart-

cluding the two lift shafts and stairwells.

porting load-bearing frame. All the walls

made from prefabricated hollow steel

are load-bearing, there are no lightweight


partition walls. Only the flights of stairs are

was built of laminated plywood. The walls

and floors form a honeycomb-like self-sup-







relatively straightforward: The existing thickness of the wood panels, combined with a layer of drywall, allowed the design team to achieve fire resistance ratings of 60 and 90 minutes.

Waugh Thistleton calculate that as much carbon is stored in the timber frame as would be emitted as CO, in operating the building during a period of around twenty years. During this time, therefore, Stadthaus will have a positive carbon footprint. Even accounting for the fact that the prefabricated timber elements were transported from Austria, there is still a saving of 120 tonnes of CO2 emissions. Interestingly the choice of building material by the client, Telford Homes, was guided not so much by ecological considerations, as purely economic ones: The architects had simply presented the facts that a timberframed construction would be faster, simpler and more cost-effective than a steelframed one of similar dimensions. The insulation on the outer walls is 70 mm thick, giving a U value of 0.27 W/m²K. Andrew Waugh sees the greatest value of this new building in its combination of sustainability and cost-effectiveness: "If this had been a project with a declared 'green' orientation, it could perhaps easily have been dismissed as an experiment. But the special attraction of Murray Grove is the very fact that it is a mainstream development which is subject to all the usual criteria in residential construction. And it has fulfilled those criteria but using a brand new type of construction."